

HD Video Communications on Display

The integrated HD video communications solution designed to streamline your business.

LGExecutive, powered by LifeSize®, is the ideal combination of an HD video communications solution and the functionality of an HD display, all in one sleek form factor. This jointly developed offering from LG and LifeSize combines HD quality performance, affordability and interoperability to maximize the return on the customer's video communications investment.

The Smart Choice for Highest Quality Experience

The solution supports 720p30 HD video calling and is a natural extension of the HD quality customers have come to expect from LifeSize. The device is also broadly interoperable with video conferencing endpoints and IP/PBX installations—enabling executives, remote office employees and teleworkers to connect face to face with anyone, anywhere.

The Simple, Integrated Solution with Easy Setup

Users will enjoy a high definition, immersive experience without worrying about setup and space required for a separate camera, video endpoint and display. Deployment is simple and takes only minutes, while the sleek 24" display fits easily on an office desk or in a small workspace.

Streamlined Business Activities and Communications

This integrated system combines HD video, camera, and wideband audio, all within an HD resolution display. Business users never have to leave the comfort of their office chairs to host or participate in an HD video call and can seamlessly switch back to PC use after their call is complete. Data in the form of presentations or other content can be shared over the network. Users can easily record video via one button recording and live streaming via LifeSize® Video Center.

LGExecutive, powered by LifeSize®

Simple. Smart. Streamlined.



LGExecutive, powered by LifeSize Key Features

HD Video Communications Point-to-point HD video calls at 720p30 HD resolution

HD Display Fully integrated HD video and wideband audio system in a 24" display with 1920x1080 HD resolution

Interoperability Broad interoperability with VTC endpoints, IP/PBX installations

Easy Setup for Quick Mainstream Deployment 2 wires to set up system: power and Ethernet

Intuitive Graphical Interface Easy switching between HD video conferencing and PC monitor functionality

Compact Form Factor Integrated 720p camera, microphone array and premium speakers

Data Transmit Share presentations during a video call via LifeSize® Virtual Link™

Live Streaming and Recording One button recording and live streaming to LifeSize® Video Center

Product Specifications

LGExecutive, powered by LifeSize®

System Components

Fully integrated display, camera, microphone, speakers, and codec
Cables

Display

24" LCD monitor
1920x1080 resolution, 16:9 aspect ratio
Contrast ratio: 50,000:1
Viewing angle: 170°/160°
Response time: 2ms (Typical)
Brightness: 310 cd/m2
Auto resolution
Antiglare surface treatment
16.7M colors

Communications

H.323, SIP
128 Kbps–2.0 Mbps

HD 720p Camera

Fixed focus with range from 241 mm (9.5") to infinity

Video Specifications/Video Resolutions

Maximum resolutions widescreen 16:9 aspect ratio
All resolutions progressive scanning
All resolutions at 30 frames per second
192 Kbps (432x240 pixels) widescreen FCIF
384 Kbps (720x400 pixels) cable TV
512 Kbps (800x488 pixels) DVD resolution
768 Kbps (1024x576 pixels) 2x DVD resolution
1.1 Mbps or higher (1280x720 pixels) high definition
Actual resolution depends on capability of remote end and is impacted by the quality of the communications channel

Video Standards

H.264, H.263, H.261 and H.239/BFCP compliant with Polycom
H.239 (transmit)—uses H.264 (requires software version 4.7 or newer and LifeSize® Virtual Link™)

Video Inputs (2 Inputs)

1 x HDMI
1 x VGA

HD Audio Input

Dual omni-directional, beam forming microphones
100 Hz up to 16 kHz

Audio Features

Built-in ringer
GIPS NetEQ packet loss concealment
Full duplex for natural conversations
Echo cancellation for echo-free calls
Automatic noise reduction
Automatic gain control

Audio Standards

G.711, G.722, G.722.1 and G.722.1C licensed from Polycom®, G.728, G.729, MPEG-4 -AAC-LC

Audio Features

HD audio
GIPS NetEQ packet loss concealment
Full duplex for natural conversations
Echo cancellation for echo-free calls
Automatic gain control
Automatic noise reduction
MicPod or Dual MicPod support (optional)

Audio Standards

G.711, G.722, G.722.1 and G.722.1C licensed from Polycom®, G.728, G.729, MPEG-4 -AAC-LC

Audio Input

1 x microphone in (3.5mm)

Audio Output

1 x line out/headset (L+R) (3.5mm)

Other Supported Standards

H.225, H.245, H.281, RFC 3261, RFC 3264, RFC 2190, RFC 3407, RFC 2833

Network Interfaces

Integrated 2-port Ethernet switch
1 x RJ-45 network LAN
1 x RJ-45 for PC connectivity

Stream/Record with LifeSize® Video Center

Stream/record video and data* outside of a call
Single button, ad-hoc recording
Recording indicator
Available with software version 4.7 or later

User Interface & Features

Context sensitive user interface
Graphical user interface call manager
Multiple languages supported
Do Not Disturb mode

Security

Admin and user-level password
SNMP security alerts
Ability to disable HTTP, SSH and Telnet services
H.235 (AES) encryption support including strict compliance
TLS/SRTP support
IEEE 802.1x support
Kensington Security Slot™

Intelligent Networking Features

Adaptive Motion Control (AMC)
NAT/firewall traversal (H.460/SIP)
IPv4 and IPv6 support
Auto bandwidth detection

Directory and Address Book

Up to 1000 local directory entries
Save, lock, remove, redial list features
Missed call notification
Auto-discovery directory lookup (patent pending)
LDAP support/H.350 compliant meetings
H.323 URI dialing support (Annex O)

System Management

SNMP
Backup and restore capability

Power

AC voltage 100–240V, 50–60 Hz

Environmental Data

Operating temperature:
0° C (32° F) to 35° C (95° F)
Operating humidity:
15% to 85%, noncondensing
Storage temperature:
-20° C (-4° F) to 60° C (140° F)
Storage humidity:
10% to 90%, noncondensing

Dimensions

Width: 23.4" (594 mm)
Depth: 2.8" (71 mm)
Height: 20.3" (515 mm)
Weight: 17.7 lbs (8.0 kg)

* Recording data requires LifeSize® Virtual Link™



AMERICAS:

LifeSize
1601 S. MoPac Expressway
Suite 100
Austin, Texas 78746 USA
+1 512 347 9300
Toll Free US +1 877 543 3749
E-mail info@lifesize.com
www.lifesize.com

EMEA:

LifeSize Regional Office
+49 89 1222 899 0 (Germany)
Toll Free Europe +00 8000 999 09 799

APAC:

LifeSize Regional Office
+65 6303 8370 (Singapore)