

Extending HD Video to Mobile Devices

With the evolution of the mobile landscape, there has never been a better time to bring HD video collaboration to every worker, in every location, on every device to enable increased collaboration and maximize productivity. Enter LifeSize ClearSea—an enterprise-class client/server solution for desktop and mobile video collaboration.

Collaborate with Anyone, Anywhere, on Any Device

Experience universal video collaboration with true mobility. LifeSize ClearSea is completely interoperable with all standards-based video systems and infrastructure solutions, also supporting the registration of H.323 and SIP devices. The LifeSize ClearSea software client offers flexible collaboration with support for PCs and Macs, Android and iOS smartphones and tablets. Powerful collaboration tools such as user groups, multiparty calling, presence and text chat, real-time data sharing with H.239 presentation, easy switching of camera view, a centralized contact list for easy directory dialing and single number reach ensure that workers can connect faster and easier than ever before.

Enterprise Solution with Superior Video Quality

LifeSize ClearSea is simple to deploy and scale across the enterprise. Designed for organizations that need to deploy HD video communication to tens, hundreds or even thousands of users, LifeSize ClearSea provides a flexible, interoperable solution for instantly connecting any desktop or mobile device to the meeting room. LifeSize ClearSea enables professional, Full HD video collaboration at 1080p for an immersive, true-to-life experience.

Minimize IT Resources and Maximize IT Investment

With the choice of a hardware appliance or virtual machine software, organizations have complete flexibility. Concurrent licensing plans eliminate hassle, cost and complexity, saving valuable IT budgets, and clustering enables enterprise scalability, geographical distribution and redundancy. Built-in automatic NAT/firewall traversal and embedded media encryption provide secure video collaboration inside or outside the organization without additional equipment or IT resources.



LifeSize ClearSea Key Features

HD Video Quality

Full HD (1080p) video with natural, full-motion video

Supported Platforms

Client software available on Windows, Mac OS X and on more than 40 Android and iOS smartphones and tablets

Video PBX

Easily create dial plans for call handling inside and outside your network

Open and Interoperable

Standards-based, endpoint agnostic; accepts calls and registrations from any H.323/SIP device

Broad Deployment

Clustering for scalability and redundancy

Licensing Options

Concurrent-use licensing per port

Flexible

Hardware appliance or virtual machine software

NAT/Firewall Traversal

Built-in NAT/firewall traversal including support for separate LAN and DMZ nodes

Multiparty Calling

Connect up to 26 participants with multiconference support

Enhanced Collaboration

H.239 presentation both on desktop and mobile and easy switching on camera view on mobile devices

LifeSize ClearSea Server

Available as hardware appliance or virtual machine software

Communications

H.323, compliant with ITU-T H.323v4, H.225v13; Call Control (H.450.2); H.235

SIP, RFC compliancy: RFC-2396, RFC-2543, RFC-2617, RFC-2822, RFC-2833, RFC-2976, RFC-3260, RFC-3261, RFC-3263, RFC-3264, RFC-3265, RFC-3311, RFC-3420, RFC-3428, RFC-3515, RFC-3581, RFC-3550, RFC-3711, RFC-3856, RFC-3859, RFC-3860, RFC-3863, RFC-3891, RFC-3960, RFC-3984, RFC-4346, RFC-4347, RFC-4488, RFC-4566, RFC-4585, RFC-4572, RFC-4961, RFC-5104, RFC-5168, RFC-5506, RFC-5577, RFC-5763, RFC-5764, RFC-5939

Supports registration of H.323 and SIP devices

Video Specifications/Video Resolutions

Up to 1080p30, up to 2 Mbps on desktop

Management

Automatic provisioning, configuration and secure authentication of LifeSize ClearSea client based on user credentials
Handles automatic update of new client releases
Ajax-powered, web-based administration console
LifeSize ClearSea desktop client one-step installation via HTTP browser

Directory and Address Book

Support user authentication with external databases and secure LDAP
User groups management
Centralized contacts directory
Import/export of CSV files for accounts creation

Additional Features

Clustering
Call routing engine
H.239 presentation
H.224, H.281 (FECC)
Multiparty (v.a.): 1080p and 30 fps, connects any SIP or H.323 endpoint, up to 26 participants, no limit in concurrent rooms, supports participants' video and content sharing (H.239)
Acts as a session border controller, handles NAT/firewall traversal
Support for configurations with LAN<->DMZ separate nodes
H.323/SIP encryption with AES
Associate H.323/SIP endpoints to LifeSize ClearSea accounts
Video IVR for dialing endpoint extensions

Virtual Machine Software Requirements

LifeSize ClearSea virtual machine software can run on:
VMware Player 3.0 or higher, VMware Workstation 7 or higher, VMware Server 2.0 or higher, VMware vSphere/ESXi 3.51 or higher

Model	Host suggested Configuration	Virtual Machine Configuration
CS100	Intel Xeon Nehalem 2 GHz+ (or better)	2 vCPU 2 GB RAM 10 GB HDD 2 vNIC
CS150	Dual Quad-core Xeon Nehalem E5620 @ 2.40 GHz (or better)	8 vCPU 3 GB RAM 10 GB HDD 2 vNIC

Hardware Appliance (CS300)

Rack mountable (1U)
Dimensions: 17.2"W x 1.7"H x 19.8"D

Environmental Data

Operating temperature: 10°C (50°F) to 35°C (95°F)
Operating humidity: 20% to 95%, noncondensing
Storage temperature: -40°C (-40°F) to 70°C (158°F)
Storage humidity: 5% to 95%, noncondensing
Weight: 17.2 kg (38 lbs)

LifeSize ClearSea Client: PC and Mac OS X

Video Standards

H.263, H.263+, H.264

Video Specifications/Video Resolutions

Supports multiple resolutions up to 1080p30 and 720p60 (receiving only)—self-adapting depending on available CPU cores

Audio Standards and Features

G.722.1 Annex-C (Polycom® Siren14™), G.722.1 (Polycom® Siren7™, 16 KHz wide-band), G.711 μ-law, A-law
Full-duplex acoustic echo canceller with audio denoise filter

Additional Features

H.239 presentation (up to 1280x768), video sharing
3-party continuous-presence multiparty without external equipment (embedded transcoding MCU capabilities)
Far-end camera control (H.224, H.281)
H.323/SIP encryption with AES
Call recording, playback and export in Windows Media Video (WMV) or Quicktime (MOV)
Instant messaging and presence
Automatic "quality vs. CPU load" dynamic adjustment
Send in-band or out-of-band DTMF
Automatic bandwidth control, adaptive to network conditions
Adaptive low-latency packet-loss recovery
Supports asymmetric input/output bandwidths (e.g., ADSL)
Languages supported: English, Russian, German, Spanish, French, Italian, Simplified Chinese, Traditional Chinese, Japanese, Korean
Web integration (start a call by clicking a web link)
Company logo in GUI (managed by LifeSize ClearSea Server administrator)

Recommended Peripherals

Webcams

Logitech HD Pro C920
Logitech HD Pro C910
Logitech HD Pro C510
Logitech for Business HD B990
Logitech for Business HD B910

Headsets

Logitech BH870 Bluetooth Headset
Logitech ClearChat Pro USB (H530)
Logitech Premium Notebook Headset

USB Speakerphones

Logitech BSP420 USB Speakerphone
ClearOne CHAT™ 50, 100

Minimum System Requirements

Windows XP/2003/Vista/7 (including 64-bit versions), DirectX 9.0c or higher
Mac OS X 10.5 Leopard or higher
Any x86 CPU with SSE2 instructions (audio/high-res video calls); Core 2 Duo class, 2.33 GHz (H.264, 720p video calls); Core 2 Quad class, 2.66 GHz (H.264, 1080p video calls); 1 GB RAM and 30 MB hard-disk space

LifeSize ClearSea Client: Mobile Devices*

Address book, call history, privacy mode switch
Instant messaging and presence
Send DTMF in-band or out-of-band
H.224, H.281 (FECC)
H.239 presentation

Video

Support for H.264 HD 720p 15 fps on new iPad and iPad2
Support for H.264 HD 720p 30 fps on Motorola Xoom and Acer Iconia
Support for qHD on selected Android devices
ITU-T H.263+ simultaneous encode/decode, up to CIF resolution (352x288), 15 fps, 384 Kbps or better on all other supported devices

Audio

G.711 μ-law, A-law

*Recommended Devices

Android™: HTC EVO™, Desire™ HD, Incredible, Sensation, myTouch® 4G, Droid Incredible II, ThunderBolt, Flyer P512, Evo 3D/Samsung Epic™, Galaxy S, Galaxy S II, Galaxy Tab, Galaxy Tab 10.1, Captivate™, Fascinate™, Vibrant™, Galaxy Nexus, Sidekick 4G, Droid Charge, Conquer/Google Nexus One, Nexus S/Dell Streak 5, Streak 7/Motorola Atrix 4G, Xoom, Droid Bionic/Acer Iconia Tab A500. This list includes only the certified devices; other Android devices might work with LifeSize ClearSea.

iOS: iPhone® 4S, iPhone® 4, iPod touch® 4th generation, new iPad, iPad™ 2, iPad™ and iPhone® 3GS (iPad™ has no video camera so only remote-party video is shown if available; iPhone® 3GS uses the only available back camera).

Available System Configurations

Model	Ports	Form Factor	Description
CS100	6/16	Virtual Machine Software	ClearSea Server as VMware image. Up to 1080p; bandwidth up to 2 Mbps per call. 200 accounts. Unlimited ClearSea Client downloads.
CS150	26/50/100	Virtual Machine Software	ClearSea Server as VMware image. Up to 1080p; bandwidth up to 2 Mbps per call. 2,500 accounts. Unlimited ClearSea Client downloads.
CS300	26/50/100	Hardware Appliance	ClearSea Server as hardware appliance. Up to Full HD 1080p; bandwidth up to 2 Mbps per call. 2,500 accounts. Unlimited ClearSea Client downloads.

Available Options

Client for Android devices
Client for iOS devices
Additional 2,500 accounts for CS150 and CS300

AMERICAS:

1601 S. MoPac Expressway
Suite 100
Austin, Texas 78746 USA
Phone +1 512 347 9300
Toll Free +1 877 543 3749
www.lifesize.com

EMEA:

LifeSize Regional Office
49 89 20 70 76 0 (Germany)
Toll Free Europe 00 8000 999 09 799

APAC:

LifeSize Regional Office
+65 6303 8370 (Singapore)